



BIMU SV

By
Carrasquet

Architectural
lighting

Lighting
Systems

LED	Tridonic
CCT	2700K
Color Consistency	3 SDCM (MacAdam)
CRI (Ra)	≥ 90%
Driver	Remote or Surface driver
Dimming	Push/Dali
Bluetooth Control	Casambi 
Voltage	Input voltage: 230V Working voltage: 24V
Power	15W, 22,5W, 30W
Reflector Material	Aluminium
Diffuser Material	PMMA
Material	Aluminium
Finishes	White (matte)  Black (matte)  Black-Orange (matte) 
Approvals	CE, EAC
Lifetime	50.000h (optimum work conditions)
Warranty	See product warranty details
IES Files	Available on the website
LDT Files	Available on the website
Modifications	Custom lengths
Mounting	Tool-friendly, plug & play system, tamper resistant. Aircraft cable suspension standard length 230 cm
Maintenance	Replacement LEDs and drivers available

CE EAC  CASAMBI   TRIDONIC

[illegible]

The ceiling attachment includes a metal retainer, while the base on the floor rests by gravity on this retainer. The luminaire allows for the installation of its canopy for power supply from the ceiling or floor.

Small tabs ensure that the power and mechanical cables enter the profile very naturally. Finishes: Matte black, matte white and matte black-orange.

B.lux