



R2 S 60 Flat Canopy

By
David Abad

Decorative
Lighting

Suspension
lamps

Technical Description				Packaging	
Degree of Protection	IP20	Regulation	PUSH/DALI	Net Weight per Item	2.00 Kg
Class	III	Light type	LED/	Box Sizes	70 x 70 x 20 cm - 98 m3
Adjustable	DIM	Light source included	Yes	Gross Weight	--
Certifications	ERAC UL LISTED	Energy classification	F		

Description

Suspension lamp in aluminum featuring a ring design, with a central cable to hang it. There is a model with flat canopy that allows you to hang the R2 from lower ceilings. Both models have LED spotlight modules that provide direct and uniform lighting. There is a third R2 model with flat canopy and indirect light called up/down. All R2 models are available with the following finishes: matte white, matte black, matte bronze, brass, natural oak and natural walnut. Made in three sizes (S60, S90 and S120).

Finishes

SHADE

 Black

 Bronze (matte)

 Natural Oak

 Natural Walnut

 White

 Brass

Collection

 R2 C

 R2 S

 R2 S USA

Codes	Luminaire	Light Source
743310F	R2 S60 FLAT CANOPY WHITE	LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743310FI	R2 S60 FLAT CANOPY UP/DOWN WHITE	DOWN: LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V UP: LED 3 x 4,5W 1638lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743311F	R2 S60 FLAT CANOPY BRONZE	LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743311FI	R2 S60 FLAT CANOPY UP/DOWN BRONZE	DOWN: LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V UP: LED 3 x 4,5W 1638lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743312F	R2 S60 FLAT CANOPY BLACK	LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743312FI	R2 S60 FLAT CANOPY UP/DOWN BLACK	DOWN: LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V UP: LED 3 x 4,5W 1638lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743313F	R2 S60 FLAT CANOPY OAK	LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743313FI	R2 S60 FLAT CANOPY UP/DOWN OAK	DOWN: LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V UP: LED 3 x 4,5W 1638lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743314F	R2 S60 FLAT CANOPY WALNUT	LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743314FI	R2 S60 FLAT CANOPY UP/DOWN WALNUT	DOWN: LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V UP: LED 3 x 4,5W 1638lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743315F	R2 S60 FLAT CANOPY BRASS	LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743315FI	R2 S60 FLAT CANOPY UP/DOWN BRASS	DOWN: LED 3 x 18W 7879lm 250mA 3000K CRI>=90 230V UP: LED 3 x 4,5W 1638lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI

DOWNLOADS

 R2_S_Assembly.pdf

 R2_S_3D.zip

 R2_S_Photometry.zip

 R2_S_2D.pdf

