



R2 S 90 Flat Canopy

By
David Abad

Decorative
Lighting

Suspension
lamps

Technical Description				Packaging	
Degree of Protection	IP20	Regulation	PUSH/DALI	Net Weight per Item	2.00 Kg
Class	III	Light type	LED/	Box Sizes	98 x 98 x 19 cm - 182 m3
Adjustable	DIM	Light source included	No/Yes	Gross Weight	--
Certifications	ERC cULus LISTED	Energy classification	F		

Description

Suspension lamp in aluminum featuring a ring design, with a central cable to hang it. There is a model with flat canopy that allows you to hang the R2 from lower ceilings. Both models have LED spotlight modules that provide direct and uniform lighting. There is a third R2 model with flat canopy and indirect light called up/down. All R2 models are available with the following finishes: matte white, matte black, matte bronze, brass, natural oak and natural walnut. Made in three sizes (S60, S90 and S120).

Finishes

SHADE

 Black

 Bronze (matte)

 Natural Oak

 Natural Walnut

 White

 Brass

Collection

 R2 C

 R2 S

 R2 S USA

Codes	Luminaire	Light Source
743320FI	R2 S90 FLAT CANOPY UP/DOWN WHITE	DOWN: LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V UP: LED 4 x 4,5W 2184lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743321F	R2 S90 FLAT CANOPY BRONZE	LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743321FI	R2 S90 FLAT CANOPY UP/DOWN BRONZE	DOWN: LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V UP: LED 4 x 4,5W 2184lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743322F	R2 S90 FLAT CANOPY BLACK	LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743322FI	R2 S90 FLAT CANOPY UP/DOWN BLACK	DOWN: LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V UP: LED 4 x 4,5W 2184lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743323F	R2 S90 FLAT CANOPY OAK	LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743323FI	R2 S90 FLAT CANOPY UP/DOWN OAK	DOWN: LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V UP: LED 4 x 4,5W 2184lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743324F	R2 S90 FLAT CANOPY WALNUT	LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743324FI	R2 S90 FLAT CANOPY UP/DOWN WALNUT	DOWN: LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V UP: LED 4 x 4,5W 2184lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743325F	R2 S90 FLAT CANOPY BRASS	LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI
743325FI	R2 S90 FLAT CANOPY UP/DOWN BRASS	DOWN: LED 4 x 18W 9755lm 250mA 3000K CRI>=90 230V UP: LED 4 x 4,5W 2184lm 250mA 3000K CRI>=90 230V DIM PUSH/DALI

DOWNLOADS

 R2_S_Assembly.pdf

 R2_S_3D.zip

 R2_S_Photometry.zip

 R2_S_2D.pdf

