



SIS Spot SR

By
María Güell &
Carrasquet

Architectural
Lighting

Collections

Description

Collection of surface and pendant spotlights manufactured in aluminium, for direct and focused lighting. They have lenses with different angles of aperture (24°, 36° and 60°). The pendant version has the options of opal glass and a striated glass accessory. SIS is available in white, black, grey and brass finishes.

Technical Description				Packaging	
Degree of Protection	IP20	Regulation	NO	Net Weight per Item	--
Class	III	Light type		Box Sizes	0
Regulable	--	Light source included	Yes	Gross Weight	--
Certifications	ERC	Energy classification	-		

Finishes

SHADE

Black (matte)

Brass (matte)

White (matte)

Grey (matte)

Collection

Sis Outdoor

Sis System

Sis Spot

Sis Spot S

Codes	Luminaire	Light Source
771700	SIS SR SPOT D40 24° BLACK	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771701	SIS SR SPOT D40 24° WHITE	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771702	SIS SR SPOT D40 24° BRASS	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771710	SIS SR SPOT D40 36° BLACK	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771711	SIS SR SPOT D40 36° WHITE	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771712	SIS SR SPOT D40 36° BRASS	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771720	SIS SR SPOT D40 60° BLACK	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771721	SIS SR SPOT D40 60° WHITE	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771722	SIS SR SPOT D40 60° BRASS	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771703	SIS SR SPOT D40 24° GREY	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771713	SIS SR SPOT D40 36° GREY	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771723	SIS SR SPOT D40 60° GREY	LED 6,3W 627lm 350mA 2700K CRI>=90 230V
771951		LED 6,3W 627lm 350mA 2700K CRI>=90 230V

