



SIS Spotlight C D60

By
María Güell &
Carrasquet

Architectural
Lighting

Collections

Description

Collection of surface and pendant spotlights manufactured in aluminium, for direct and focused lighting. They have lenses with different angles of aperture (24°, 36° and 60°). The pendant version has the options of opal glass and a striated glass accessory. SIS is available in white, black, grey and brass finishes.

Technical Description				Packaging	
Degree of Protection	IP20	Regulation	NO	Net Weight per Item	--
Class	III	Light type		Box Sizes	0
Regulable	--	Light source included	Yes	Gross Weight	--
Certifications	ERC	Energy classification	-		

Finishes

SHADE

Black (matte)

Brass (matte)

White (matte)

Grey (matte)

Collection

Sis Outdoor

Sis System

Sis Spot

Sis Spot S

Codes	Luminaire	Light Source
771580	SIS C SPOTLIGHT D60 26° BLACK	LED 8W 635lm 2700K CRI>=90 230V
771581	SIS C SPOTLIGHT D60 26° WHITE	LED 8W 635lm 2700K CRI>=90 230V
771582	SIS C SPOTLIGHT D60 26° BRASS	LED 8W 635lm 2700K CRI>=90 230V
771590	SIS C SPOTLIGHT D60 40° BLACK	LED 8W 635lm 2700K CRI>=90 230V
771591	SIS C SPOTLIGHT D60 40° WHITE	LED 8W 635lm 2700K CRI>=90 230V
771592	SIS C SPOTLIGHT D60 40° BRASS	LED 8W 635lm 2700K CRI>=90 230V
771583	SIS C SPOTLIGHT D60 26° GREY	LED 8W 635lm 2700K CRI>=90 230V
771593	SIS C SPOTLIGHT D60 40° GREY	LED 8W 635lm 2700K CRI>=90 230V

DOWNLOADS

