



Code

6397

Description

IP67 walkable recessed spotlight with diffused light with AISI 316L stainless steel flange, aluminum heat sink, frosted glass screen and 30cm neoprene cable.

Year of production

2016

Typology

recessed ceiling wall ground

Material

INOX AISI 316L

Light emission

direct

IP grade

67

Finishes

.33



Brushed steel

Allimentation

500mA - 17,5Vdc

Technical Data

/W 8.9W 1016 lm (1223 lm source) - 4000K - CRI>90

/WW 8.9W 960 lm (1156 lm source) - 3000K - CRI>90

/XW 8.9W 918 lm (1106 lm source) - 2700K - CRI>90

Optical grade

28°

60°

Net weight


0,88 lb




11,81 inch



2,36 inch



3,14"



Ø 2,75"

ACCESSORIES



Kit draining junction box + IP connector Kit draining junction
box + IP connector

0230

0,20 lb



0127

0,14 lb



0128

0,14 lb



Multi-power dimmable driver PUSH - 1...10V, 2-11 Spot
350mA 500mA

0141/DIM

0,00 lb

.DIM  DIM

ACCESSORIES



0141/DALI 0,22 lb
.DALI  DALI



0145 0,47 lb



Multi-power DALI dimmable driver, 1-21 Spot
mA 350 500

0145/DALI 0,47 lb
.DIM  1-10V-PUSH
.1-10V  1-10V
.DALI  DALI