



Code **6411**

Description IP67 walkable adjustable recessed spotlight with diffused light with AISI 316L stainless steel flange, aluminum heat sink, frosted glass screen and 30cm neoprene cable.

Year of production 2013

Typology recessed ceiling wall ground

Material INOX AISI 316L

Light emission direct

IP grade 67

Finishes **.33**  Brushed steel

Allimentation 500mA - 2,9Vdc

Technical Data
/W 2W (209 lm source) - 4000K - CRI>90
/WW 2W (199 lm source) - 3000K - CRI>90
/XW 2W (189 lm source) - 2700K - CRI>90

Optical grade
 11°
 25°
 45°



Net weight 0,49 lb



11,81 inch



2,36 inch



6 cm

ACCESSORIES



Kit draining junction box + IP connector Kit draining junction box + IP connector

0230

0,20 lb



Wall formwork Wall plastic Box

0232

0,13 lb



0127

0,14 lb



Multi-power dimmable driver PUSH - 1...10V, 2-11 Spot 350mA 500mA

0141/DIM
.DIM  DIM

0,00 lb

ACCESSORIES



0141/DALI 0,22 lb
.DALI ➤ DALI



0145 0,47 lb



Multi-power DALI dimmable driver, 1-21 Spot
mA 350 500

0145/DALI 0,47 lb
.DIM  1-10V-PUSH
.1-10V  1-10V
.DALI ➤ DALI